



Pneumatic Conveying



DensePhase Denseveyor

Pneumatic Bulk Solids Handling
Document No. CPC-INF-2030

The Clyde Denseveyor system is a simple, effective and highly reliable method of conveying a wide range of materials from a single collection point.

Originally developed for the foundry industry the Denseveyor has been established to reliably handle the widest range of materials from fine cohesive powders to large pellets.

The Denseveyor conveying velocities are low ensuring minimal degradation of friable materials.

Phone

+44 01302 552200

Email

sales@clydepc.co.uk

Web

www.clydepc.co.uk



ISO9001 | ISO14001



British Engineering

Key Features

Wide Range of Sizes Available

These machines range from 0.08 - 2.8 cu.m giving it a respectable conveying capacity ranging from 1.0 - 50 tph at distances up to 300m

Various Fluidising Discharge Aids

Internal skirts, fluidising ports, OBCR and ABR can be added to ensure flow is consistent

Pre-assembled

Fully assembled and pre-wired in the factory to ensure site installation activity is minimised

Heavy Duty Pneumatic Valves

Fitted with the original Dome Valve throughout, the Denseveyor is highly reliable even in the most difficult of applications

Benefits

Low Degradation

Low velocity conveying ensures minimal degradation of friable materials

Extremely Reliable

Incorporating only tried and tested key components resulting in highly reliable operation in a wide range of applications

Extremely Efficient

High phase densities make this one of the most energy efficient conveying machines on the market

Unique Actuation

The Dome Valve can cut through moving or static columns of bulk material



Custom Features

Dome Coatings

Electro-nickle plating or Polymer coating for cohesive and abrasive materials

Temperature Rating

Water-cooling to achieve operating temperatures beyond 200 deg C up to 450 deg

Instrumentation

Instruments can be upgraded to meet various standard including ATEX

Pneumatic Piping

Standard nylon piping can be upgrading to suit plant specification (stainless, copper, UPVC coated copper etc)